

360° MULTI-SENSOR PTZ COMBO POD

The AXIS Q6000 4 Sensor
Camera with the AXIS Q6075-E
40X PTZ Camera



AXIS Q6075-E PTZ with the 4 Sensor Q6000 for Situational Awareness. 360° Multi-Sensor & PTZ Combo Camera is ideal for city surveillance applications. It features four 2-megapixel sensors and integrates with AXIS Q60-E/Q61-E PTZ Network Cameras, creating a solution that goes from overview to detail in a single click.

Key Features:

- **AXIS Q6075-E Outdoor PTZ** with HDTV 1080p, 40x zoom and Zipstream 2.0, with built in analytics: highlight compensation, object removed, enter/exit detection, autotracking, and Active Gatekeeper. AXIS Q6000-E Full 360° overview, One-click PTZ control, Exchangeable and tiltable lenses.
- **Strong lightweight aircraft aluminum NEMA 4X enclosure**, environmentally sealed whose components are industrialized for a long-lasting deployment in harsh conditions and temperatures of -20°~70°C; -4°~158°F
- **Solar radiation reflector** for reduced solar radiation heat transfer and cooler interior operating temperatures
- **Multiple Power inputs available** - 120VAC by default with higher power inputs available (240VAC, 277VAC, 440VAC, Solar, etc.) with short circuit, overload, over voltage and overtemperature protection
- **PoE Network Switch & Communications:** 4 Port PoE+ 90W 1G with 1 Uplink Port, 6kv Lightning Protection
- **Multiple cabling management options:** wire glands for direct cabling for power, wireless communication radios and multiple custom conduit opening options ½", ¾" & 1"
- **Exterior led power indicator light** for "from the ground" power source verification
- **Interior fused power disconnect bus**, lifetime warranty power supply providing conditioned power & surge suppression
- **Pole Mount & Surface Mount included**
- **¼ turn twist latch.** Keyed Lock(s) available

360° MULTI-SENSOR PTZ COMBO POD



Specifications:

- **Part Number:** E-IOT-POD-XL-Q60/6075-E Combo
- **Power Input:** 120VAC(Default), Options for Higher Voltages and Solar Power
- **Power Consumption:** 18W Average
- **Network Connectivity:** 1 Gbps Ethernet, Options for LTE, Wi-Fi, MM Wav & Fiber available
- **Storage:** Any VMS Software, Compatible Cloud VMS & microSDXC
- **Enclosure:** NEMA 4X Aluminum IP56
- **Operational Temperature:** -20°~70°C; -4°~158°F
- **Camera Resolution:** 1920x1080 to 160x90
- **Lens:** Q6000-qty 4 1.37mm 360° 4.44-142.6 mm, F1.6-4.41, HFOV: 62.8°-2.23°, VFOV: 36.8°-1.3°; Pan: 360° endless, 0.05° - 450°/s
- **Tilt:** 220°, 0.05°-450°/s; 32x optical zoom and 12x digital zoom, total 384x zoom
- **Warranty:** 3 Years
- **Dimensions:** 21 X 12.5 X 31 IN.
- **Weight:** 38.6 LB.

Additional Options:

- ✓ **LED Deterrent Lights**
Blue, Green, Red or Amber LED Deterrent Lights as an option.
- ✓ **>240VAC, 277VAC or 200-500VAC Power Input Available**
- ✓ **Network Communication Options**
Standard - Gigabit Ethernet 4PoE+ and 1 1G Ethernet Uplink Ethernet Switch
Optional Fiber - Gigabit Ethernet 4PoE+ and 1 Ethernet Uplink & 1 SFP Fiber Switch
- ✓ **Add Wireless P2P/P2MP Radios**
Sub 6 GHz, 5G millimeter wave, LORA for low bandwidth sensors and many more options available. Cellular 4G/5G: we offer many industrialized cellular routers and antenna for AT&T, AT&T FirstNet, T-Mobile, Verizon, Sprint & Regional Carriers, or you can provide your own SIM card.
- ✓ **ISO IoT Health Monitoring & Self-Healing Technology with or without SMA**
Watchdog Self-healing technology with email notification when a sensor, connection or equipment becomes unresponsive. This option requires ISO Network Engineering and custom configuration.

 [smartcity.com](https://www.isosmartcity.com)

ISO Network Contact:



sales@isosmartcity.com



(678) 885-9210



2100 Barrett Park Drive, #508, Kennesaw, GA 30144