

# AXIS 40x Zoom PTZ Camera POD

The AXIS Q6075-E Color at  
Night PTZ Camera



The AXIS Q6075-E delivers superior 1080p and 40x optical zoom. It features Axis Lightfinder 2.0 which captures low-light images in color and, Zipstream with support for H.264 and H.265 preserves all the important forensic detail you need, while significantly lowering bandwidth and storage requirements.

## Key Features:

- **AXIS Q6075-E Outdoor PTZ** with HDTV 1080p, 40x zoom, lightfinder 2.0 and Zipstream, with built in analytics: highlight compensation, object removed, enter/exit detection, autotracking, and Active Gatekeeper
- **Strong lightweight aircraft aluminum enclosure**, environmentally sealed whose components are industrialized for a long-lasting deployment in harsh conditions and temperatures of -20°~70°C; -4°~158°F
- **Solar radiation reflector** for reduced solar radiation heat transfer and cooler interior operating temperatures
- **Multiple Power inputs available** - 120VAC by default with higher power inputs available (240VAC, 277VAC, 440VAC, Solar, etc.) with short circuit, overload, over voltage and overtemperature protection
- **PoE Network Switch & Communications:** 4 Port PoE+ 30W 1G with 1 Uplink Port, 6kv Lightning Protection
- **Multiple cabling management options:** wire glands for direct cabling for power, wireless communication radios and multiple custom conduit opening options ½", ¾" & 1"
- **Exterior led power indicator light** for "from the ground" power source verification
- **Interior fused power disconnect bus**, lifetime warranty power supply providing conditioned power & surge suppression
- **Pole Mount & Surface Mount included**
- **¼ turn twist latch.** Keyed Lock(s) available

# AXIS 40x Zoom PTZ Camera POD



## Specifications:

- **Part Number:** E-IOT-POD-XL-Q6075-E
- **Power Input:** 120VAC(Default), Options for Higher Voltages and Solar Power
- **Power Consumption:** 30W Average
- **Network Connectivity:** 1 Gbps Ethernet, Options for LTE, Wi-Fi, MM Wav & Fiber available
- **Storage:** Any VMS Software, Compatible Cloud VMS & microSDXC
- **Enclosure:** NEMA 4X Aluminum IP56
- **Operational Temperature:** -20°~70°C; -4°~158°F
- **Storage Temperature:** -40°~85°C
- **Camera Resolution:** 1920x1080 to 160x90
- **Lens:** 4.25-170 mm, F1.6-4.95
- **Horizontal Field of View:** 65.1°-2.00° (1080p)
- **Vertical Field of View:** 39.1°-1.18° (1080p)
- **Warranty:** 3 Years
- **Dimensions:** 21 X 12.5 X 28 IN.
- **Weight:** 30.8 LB.

## Additional Options:


- ✓ **LED Deterrent Lights**  
Blue, Green, Red or Amber LED Deterrent Lights as an option.
- ✓ **>240VAC, 277VAC or 200-500VAC Power Input Available**
- ✓ **Network Communication Options**  
*Standard* - Gigabit Ethernet 4PoE+ and 1 1G Ethernet Uplink Ethernet Switch  
*Optional Fiber* - Gigabit Ethernet 4PoE+ and 1 Ethernet Uplink & 1 SFP Fiber Switch
- ✓ **Add Wireless P2P/P2MP Radios**  
Sub 6 GHz, 5G millimeter wave, LORA for low bandwidth sensors and many more options available. Cellular 4G/5G: we offer many industrialized cellular routers and antenna for AT&T, AT&T FirstNet, T-Mobile, Verizon, Sprint & Regional Carriers, or you can provide your own SIM card.
- ✓ **ISO IoT Health Monitoring & Self-Healing Technology with or without SMA**

Watchdog Self-healing technology with email notification when a sensor, connection or equipment becomes unresponsive. This option requires ISO Network Engineering and custom configuration.

 [smartcity.com](http://smartcity.com)

### ISO Network Contact:

 [sales@isosmartcity.com](mailto:sales@isosmartcity.com)

 (678) 885-9210

 2100 Barrett Park Drive, #508, Kennesaw, GA 30144