

# AXIS Laser Focus PTZ Camera POD

The AXIS Q6155-E Laser Focus  
PTZ with Speed Dry

The AXIS Q6155-E PTZ provides instantaneous focus especially in low light. It uses advanced laser technology to always give flawless focus – even in the dark. This camera is ideal for city surveillance, critical infrastructure and other applications where focus on moving objects and fast-changing scenes is needed.



## Key Features:

- **AXIS Q6155-E Outdoor PTZ** with HDTV 1080p, Laser Focus, 30x zoom and Zipstream, with built in analytics: highlight compensation, object removed, enter/exit detection, autotracking, and Active Gatekeeper
- **Strong lightweight aircraft aluminum NEMA 4X enclosure**, environmentally sealed whose components are industrialized for a long-lasting deployment in harsh conditions and temperatures of -20°~70°C; -4°~158°F
- **Solar radiation reflector** for reduced solar radiation heat transfer and cooler interior operating temperatures
- **Multiple Power inputs available:** 120VAC by default with higher power inputs available (240VAC, 277VAC, 440VAC, Solar, etc.) with short circuit, overload, over voltage and overtemperature protection
- **PoE Network Switch & Communications:** 4 Port PoE+ 90W 1G with 1 Uplink Port, 6kv Lightning Protection
- **Multiple cabling management options:** wire glands for direct cabling for power, wireless communication radios and multiple custom conduit opening options ½", ¾" & 1"
- **Exterior led power indicator light** for "from the ground" power source verification
- **Interior fused power disconnect bus**, lifetime warranty power supply providing conditioned power & surge suppression
- **Pole Mount & Surface Mount included**
- **¼ turn twist latch.** Keyed Lock(s) available

# AXIS Laser Focus PTZ Camera POD



## Specifications:

- **Part Number:** E-IOT-POD-XL-Q6155-E
- **Power Input:** 120VAC(Default), Options for Higher Voltages and Solar Power
- **Power Consumption:** 18W Average
- **Network Connectivity:** 1 Gbps Ethernet, Options for LTE, Wi-Fi, MM Wav & Fiber available
- **Storage:** Any VMS Software, Compatible Cloud VMS & microSDXC
- **Enclosure:** NEMA 4X Aluminum IP56
- **Operational Temperature:** -20°~70°C; -4°~158°F
- **Camera Resolution:** 1920x1080 to 160x90
- **Lens:** 4.3 - 129 mm, F1.8 HFOV: 66.7°-2.36° VFOV: 39.5°-1.37°; Laser focus: Pan: 360° endless, 0.05°-700°/s
- **Tilt:** +20 to -90°, 0.05°-500°/s
- **Zoom:** 30x optical, 12x digital, total 360x zoom
- **Warranty:** 3 Years
- **Dimensions:** 21 X 12.5 X 28 IN.
- **Weight:** 30.8 LB.

## Additional Options:

- ✓ **LED Deterrent Lights**  
Blue, Green, Red or Amber LED Deterrent Lights as an option.
- ✓ **>240VAC, 277VAC or 200-500VAC Power Input Available**
- ✓ **Network Communication Options**  
*Standard* - Gigabit Ethernet 4PoE+ and 1 1G Ethernet Uplink Ethernet Switch  
*Optional Fiber* - Gigabit Ethernet 4PoE+ and 1 Ethernet Uplink & 1 SFP Fiber Switch
- ✓ **Add Wireless P2P/P2MP Radios**  
Sub 6 GHz, 5G millimeter wave, LORA for low bandwidth sensors and many more options available. Cellular 4G/5G: we offer many industrialized cellular routers and antenna for AT&T, AT&T FirstNet, T-Mobile, Verizon, Sprint & Regional Carriers, or you can provide your own SIM card.
- ✓ **ISO IoT Health Monitoring & Self-Healing Technology with or without SMA**  
Watchdog Self-healing technology with email notification when a sensor, connection or equipment becomes unresponsive. This option requires ISO Network Engineering and custom configuration.

ISOsmartcity.com

### ISO Network Contact:

✉ [sales@isosmartcity.com](mailto:sales@isosmartcity.com)

☎ (678) 885-9210

📍 2100 Barrett Park Drive, #508, Kennesaw, GA 30144